

THE ULTIMATE BLEND  
OF STYLE AND PERFORMANCE

## CELEBRITY® DX SPORT

The **Celebrity® DX Sport** delivers easy operation, high performance, and sleek style. Loaded with standard features like an increased top speed, larger rear wheels and upgraded electronics, the Celebrity DX Sport is equipped to excite.




**Pride**<sup>®</sup>  
Mobility Products  
Australia Pty. Ltd.

(Tel) 03 9706 4611 • (Fax) 03 9706 4622 • [www.pridemobility.com](http://www.pridemobility.com)

# Celebrity® DX Sport 4-wheel

Weight capacity:	159 kg (350 lbs.)
Maximum speed:	Up to 12.87 km/h (8 mph)
Ground clearance:	8.26 cm (3.25") (at motor)
Turning radius:	145 cm (57")
Overall length:	119 cm (47")
Overall width:	61 cm (24")
Wheels:	
Front:	9 cm x 25 cm (3.5" x 10")
Rear:	10 cm x 33 cm (4" x 13")
Anti-tips:	Rear
Suspension:	Rear
Transport weight	
Total w/o batteries:	65 kg (143 lbs.)
Heaviest piece when disassembled:	31.29 kg (69 lbs.) (front section)
Drive train:	Sealed transaxle, 24 volt DC motor
Dual braking system:	Electronic, regenerative and electromechanical (electronic, regenerative disc brakes)
Std. Seating:	CRS Deluxe seat with headrest and manual recline
Battery charger:	Off-board, 5 amp (standard)
Per-charge range:	Up to 40 km (25 miles)
Battery requirements:	(2) 12V deep cycle (AGM or gel cell type recommended)
Battery size:	40 AH: 11 kg (24.5 lbs.) <sup>1</sup> each
Warranty:	2-year limited warranty

Colours:



<sup>1</sup>Battery weight may vary based on manufacturer

<sup>2</sup>Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).

<sup>3</sup>Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

## FEATURES

- State-of-the-art rear suspension
- Larger rear wheels
- Top speed of up to 12.87 km/h (8 mph)
- Maximum weight capacity of 159 kg (350 lbs.)
- Ultra-simple, auto-latching lockup for quick disassembly/reassembly
- Easily accessible tie down points (for transport of unoccupied scooter)
- Front basket and rearview mirror standard
- Tight turning radius of 145 cm (57")
- Includes standard angle-adjustable dual bulb kerb light
- Front frame-mounted seat post for optimal stability
- High visibility reflectors
- Microprocessor-based controller
- Tiller rotation lock permits tiller to be used as a handle during transport

## OPTIONS

- Cane/crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Walker holder