



# Jazzy<sup>®</sup>

## SELECT

The easily maneuverable, Jazzy Select<sup>®</sup> is equipped with performance features like Active-Trac<sup>®</sup> Suspension and in-line motor technology for enhanced efficiency, torque and range for high performance. With features like a Contour high-back seat with a headrest, full length armrests and black, non-scuffing tyres with silver rims, the Jazzy Select is a superb overall value.



**Pride<sup>®</sup>**  
Mobility Products  
Australia Pty. Ltd.  
— LIVE YOUR BEST —

## SPECIFICATIONS

<b>Weight capacity</b>	Up to 136 kg (300 lbs.)
<b>Maximum speed<sup>1</sup></b>	Up to 6.44 km/h (4 mph)
<b>Ground clearance</b>	4.604 cm (1.813") at rear frame skid plate
<b>Turning radius<sup>2</sup></b>	55.25 cm (21.75")
<b>Overall length<sup>2</sup></b>	91.44 cm (36") without front riggings
<b>Overall width<sup>2</sup></b>	60.33 cm (23.75")
<b>Drive wheels</b>	25.4 cm (10") solid
<b>Anti-tips</b>	12.7 cm (5") solid, rear-mounted
<b>Castors</b>	15.24 cm (6") solid, rear-mounted
<b>Suspension</b>	Active-Trac <sup>®</sup>
<b>Drivetrain</b>	Two-motor, mid-wheel drive
<b>Braking system</b>	Intelligent braking (electronic, regenerative disc brakes)
<b>Standard electronics</b>	40 amp, PG GC 3 controller
<b>Standard seat</b>	High-back
<b>Specialty controls</b>	N/A
<b>Battery charger</b>	Off-board, 3.5 amp
<b>Per-charge range<sup>1,4</sup></b>	Up to 20.8 km (12.92 miles)
<b>Battery requirements<sup>5</sup></b>	(2) 12 volt deep-cycle
<b>Battery size (largest)</b>	(U-1) 30-34 AH
<b>Battery weight<sup>3</sup></b>	10 kg (22 lbs.) each
<b>Base weight</b>	46.5 kg (102.5 lbs.)
<b>Standard seat weight</b>	19 kg (42.5 lbs.) (high-back)
<b>Max. seating dimensions</b>	50.8 cm x 50.8 cm (20" x 20")
<b>Warranty</b>	2-year limited

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.

- 1) Range and speed vary with user weight, terrain type, battery charge, battery condition and tyre pressure. This specification can be subject to a variance of (+ 10% or - 5%) .
- 2) Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 3) Battery weight may vary based on manufacturer.
- 4) Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4, standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities. This specification can be subject to a variance of +10%, -5%.
- 5) AGM or gel cell type required

## FEATURES

- New black, non-scuffing tyres with silver rims
- Larger foot platform
- 40 amp, PG GC 3 controller
- Built with ease of service in mind
- Easy side access to batteries
- Toolless front panel access to electronics to minimise service time
- Active-Trac<sup>®</sup> Suspension

## OPTIONS

- High-back seat with solid seat pan
- Cup holder
- Weather cover
- Rear basket
- Oxygen tank holder
- Cane/crutch holder
- Walker holder

## COLOUR



Jazzy Red